




Colorama® 2 Bioactive



400



410



429





















B6

Colorama 2 Bioactive – Based on the Silent Gliss bestseller, Colorama 2 Bioactive is made with fibres containing ionised silver. Its lasting antimicrobial effect is useful in situations that have special hygiene requirements as in hospitals, nursing and retirement homes, schools, etc.










Colorama 2 Bioactive – Antibakterieller Stoff, ideal geeignet für Situationen mit speziellen hygienischen Anforderungen wie Spitaler, Altersheime, Geburtshuser und Schulen etc. Die Wirkung von Colorama 2 Bioactive basiert auf im Garn eingearbeiteten Silberionen. Gleiche Webart wie der Silent Gliss Bestseller Colorama 2.










Colorama 2 Bioactive – Bas sur l’incontournable Colorama, ce tissu intgre des fibres contenant un fil ionisant. Son effet durable antimicrobien est utile dans les lieux o une hygine est ncessaire, comme les hpitaux, crches, coles, maisons de retraite, etc.

Characteristic / Eigenschaften / Proprits	
 Transparency / Transparenz / Transparence	Semi transparent / Halbtransparent / Semi-transparent
 Fabric qualities / Ausrstung / Qualits	stiff and soft / versteift und deko / enduit et souple
 Composition / Materialzusammensetzung / Composition DIN 60 001	 100% Polyester Trevira CS (50% Bioactive)
 Weight / Gewicht / Poids (g/m ²) DIN EN 12127	290
 Thickness / Dicke / Epaisseur (mm) DIN EN ISO 2286-3	0.55
 Max. width / Nutzbreite / Largeur (cm)	335
 Widths on stock / Lagerbreiten / Largeurs en stock (cm)	340, 202, 138,  12.7, 8.9
 Flame retardant / Schwerentflammbarkeit / Classement au feu	B1 (DIN 4102-1), M1 (NF P 92-503-507), BS 5867-2, B-s1 (EN 13501)
 Colour fastness / Lichtechtheit / Rsistance  la lumire DIN EN ISO 105-B02	5-7
 Applicable in humid areas / Feuchtraumgeeignet / Compatible avec lieux humides	Yes / Ja / Oui
 Special colours minimum order quantity / Spezialfarben erhltlich ab / Couleurs spciales disponibles  partir de	240 m
 Suitable for Skylight systems / geeignet fr Skylight-Systeme / adapt pour les systmes Skylight	Silent Gliss 8700, 2190, 2195
 Green building  	This fabric can assist in the achievement of green building ratings. Dieser Stoff kann zum Erreichen von Green building-Zertifizierungen beitragen. Ce tissu peut permettre d’atteindre les certifications Green building.

Washing instructions / Pflegehinweis / Nettoyage	
	approx. 1% shrinking possible ca. 1% Schrumpfung mglich 1% de rtrcissement possible

Processing / Verarbeitung / Traitement	soft / deko / souple	stiff / versteift / enduit
Welding / Schweien / Soudure	<input type="checkbox"/>	<input type="checkbox"/>
Individual design / Individuelles Design / Design individuel		
Digital printing / Digitaldruck / Impression digitale	★★☆	
Laser cutting / auslasern / Coupe au laser	<input type="checkbox"/>	

Optical and solar coefficients / Optische und Solar-Kennzahlen / Coefficients optiques et solaires (DIN EN 410)			
Colour / Farbe / Couleur	400	410	429
 Tv	35.2	36.3	10.8
 Rv	60.8	62.0	31.1
 Av	4.0	1.7	58.1
 Ts	34.0	34.4	22.9
 Rs	58.2	59.2	46.2
 As	7.8	6.4	30.9
 Tuv	4.6	8.4	6.3
 Fc	0.60	0.60	0.60
 got	0.40	0.40	0.50

 Tv	Visible light transmission / Lichttransmission / Transmission de lumire visible (%)	 Ts	Solar transmission / Strahlungstransmission / Transmission solaire (%)
 Rv	Visible light reflectance / Lichtreflexion / Rflexion de lumire visible (%)	 Rs	Solar reflectance / Strahlungsreflexion / Rflexion solaire (%)
 Av	Visible light absorption / Lichtabsorption / Absorption de lumire visible (%)	 As	Solar absorption / Strahlungsabsorption / Absorption solaire (%)
 Tuv	UV transmission / UV-Transmission / Transmission UV (%)	 Fc	Shading factor / Abminderungsfaktor / Facteur d’ombre (EN 14501)
All coefficients may have a tolerance of +/-5% / Alle Werte sind Nennwerte mit einer Toleranz von +/-5% / Tous les coefficients peuvent avoir une tolrance de +/-5%		 got	Total g-value / Gesamt g-Wert / Valeur g totale (DIN EN 13363-1)
		(Glass g-value: 0,72; 1,6 W/m ² K) (Glas g-Wert: 0,72; 1,6 W/m ² K) (Valeur g de la vitre: 0,72; 1,6 W/m ² K)	

